

CALABOND WDH

Usage Instructions:

Calabond Glue is used for adhesion of all kinds of Wood, Ply Chipboard, Formica, wall papers etc.

- Clean and dry the gluing area & ensure that the surface should be free from dirt, grease, oil etc.
- Apply with the help of a brush, wooden piece or any machine.
- Press both surfaces firmly into place for 3 to 4 hours.



CALABOND WDPH

Usage Instructions:

Calabond Glue is used for adhesion of all kinds of Wood, Ply Chipboard, Formica, wall papers etc.

- Clean and dry the gluing area & ensure that the surface should be free from dirt, grease, oil etc.
- Apply with the help of a brush, wooden piece or any machine.
- Press both surfaces firmly into place for 3 to 4 hours.



CALABOND WDM

Usage Instructions:

Calabond Glue is used for adhesion of all kinds of Wood, Ply Chipboard, Formica, wall papers etc.

- Clean and dry the gluing area & ensure that the surface should be free from dirt, grease, oil etc.
- Apply with the help of a brush, wooden piece or any machine.
- Press both surfaces firmly into place for 3 to 4 hours.



CALABOND WD5

Usage Instructions:

Calabond Glue is used for adhesion of all kinds of Wood, Ply Chipboard, Formica, wall papers etc.

- Clean and dry the gluing area & ensure that the surface should be free from dirt, grease, oil etc.
- Apply with the help of a brush, wooden piece or any machine.
- Press both surfaces firmly into place for 3 to 4 hours.



CALABOND WD2

Usage Instructions:

Calabond Glue is used for adhesion of all kinds of Wood, Ply Chipboard, Formica, wall papers etc.

- Clean and dry the gluing area & ensure that the surface should be free from dirt, grease, oil etc.
- Apply with the help of a brush, wooden piece or any machine.
- Press both surfaces firmly into place for 3 to 4 hours.



CALABOND WD10

Usage Instructions:

Calabond Glue is used for adhesion of all kinds of Wood, Ply Chipboard, Formica, wall papers etc.

- Clean and dry the gluing area & ensure that the surface should be free from dirt, grease, oil etc.
- Apply with the help of a brush, wooden piece or any machine.
- Press both surfaces firmly into place for 3 to 4 hours.



CALABOND WD20

Usage Instructions:

Calabond Glue is used for adhesion of all kinds of Wood, Ply Chipboard, Formica, wall papers etc.

- Clean and dry the gluing area & ensure that the surface should be free from dirt, grease, oil etc.
- Apply with the help of a brush, wooden piece or any machine.
- Press both surfaces firmly into place for 3 to 4 hours.



CALABOND WDP

Usage Instructions:

Calabond Glue is used for adhesion of all kinds of Wood, Ply Chipboard, Formica, wall papers etc.

- Clean and dry the gluing area & ensure that the surface should be free from dirt, grease, oil etc.
- Apply with the help of a brush, wooden piece or any machine.
- Press both surfaces firmly into place for 3 to 4 hours.



CALABOND WD

Usage Instructions:

Calabond Glue is used for adhesion of all kinds of Wood, Ply Chipboard, Formica, wall papers etc.

- Clean and dry the gluing area & ensure that the surface should be free from dirt, grease, oil etc.
- Apply with the help of a brush, wooden piece or any machine.
- Press both surfaces firmly into place for 3 to 4 hours.



CALABOND PLUS


Calabond Plus Glue is a highly quality PVA adhesive. It dries clear and is ideal for use on wood, ply, chipboard, Formica, wall papers etc. Calabond Plus provides a high strength bond and termite resistance.

The Calabond Plus spout Pack is easy-to-use, carry and store, when not in use, tighten cap to lock out moisture and air.

Usage Instructions:

Calabond Glue is used for adhesion of all kinds of Wood, Ply Chipboard, Formica, wall papers etc.

- Clean and dry the gluing area & ensure that the surface should be free from dirt, grease, oil etc.
- Apply with the help of a brush, wooden piece or any machine.
- Press both surfaces firmly into place for 3 to 4 hours.



CALABOND SUPER GLUE

Calabond Super glue can be used to join all things like steel, iron, aluminum, glass, marble, stones, ceramics, rubber, wood, etc in a few seconds. It guarantees a reliable bond.



MANUFACTURED BY:

LUCKY CORE INDUSTRIES LIMITED

Chemicals & Agri Sciences Business
5, West Wharf, Karachi
UAN: 111-100-200

www.luckycore.com



LUCKY CORE INDUSTRIES



CALABOND

اعتماد، مضبوطی، پائیداری

Product Catalogue
Adhesive



MANUFACTURED BY
LUCKY CORE INDUSTRIES LIMITED
Formerly ICI Pakistan Limited